

T12290

Magnetic Base Dial Indicator - Reads in .001" Increments - for GE Engines and Other Miscellaneous Uses



The magnetic base dial indicator is used to check the crankshaft thrust clearance and various backlash readings. The high precision gage comes with .0005 dial increments, and the magnetic base is controlled with a button built onto the base. The gage also comes with an extension and a swivel adapter for easy adjustments.

T15491

Hand Held Contact / Non-Contact Tachometer



This hand held tachometer kit includes 5 speed tips, male and female cones and an extension.

Speed: 0-200 RPM
Range: 0-2,000RPM
0-20,000RPM
Accuracy: +1/2 of 1% full scale

T19951

Crankcase Overpressure Switch Tester for GE FDL Engines



This tool is useful in setting pressure trip points on crankcase overpressure switches and in trouble shooting engines that have been reported with COP trips.

The gauge is calibrated for +/- 0-20 inches of water.

T19951HP

Pump with Gage for T19951 Crankcase Overpressure Switch Tester



T22062

Preturbine Temperature Measuring Kit (-40 to 1999 Degrees F)



The preturbine temperature measuring kit features a digital instrument with direct readings from -40 to +1,999 F. A chart is attached to the back of the instrument to convert 0 F to 0 C. It is powered by a 9V alkaline battery (radio type). The thermocouple used is of the type K variety.

NOTE: The red wire in the thermocouple extension should always be connected to the negative terminal.

T22062 Preturbine Temperature Measuring Kit

- 1 [T22072](#) Digital Instrument
- 2 [T22090](#) Connector - Male
- 3 [T50260](#) Adapter (instrument to thermocouple lead)
- 4 [T22100](#) Thermocouple Probe - (6 in kit)
- 5 [T22110](#) 100' thermocouple extension type K

T54210

Test Gauge Kit - 0-60 PSI Gauge, 0-100 PSI Gauge, 0-200 PSI Gauge, With Hansen 2-HK Series Sockets



This kit has three heavy duty glycerin filled pressure gauges (0-60, 0- 100, 0-200 PSI) equipped with Hansen 2-HK Series Sockets. It is used to take pressure readings on locomotives equipped with test fittings. The kit comes complete with a metal box.

All gauges in this kit are available for individual sale. Also available are 30 PSI (T54210-30) and 160 PSI (T54210-160) gauges

T54860

Radiator Cap Tester



This tester is equipped with a 30 PSI glycerin filled gage calibrated to a 1-1/2% full range specification. Shop air is connected to the tester and manifold test pressure is established with a precision regulator mounted on the face of the tester. Three test receptacles are provided to test three tang caps, 2 tang caps and the newer smaller diameter EMD Cap. The test receptacles are manufactured with heat treated alloy steel and are plated to minimize wear and rusting.

T64841

Capacitor Discharge Device - for All GE AC Locomotives



T64930

Decade Box(Tier 0 & Tier 1) *



T66020

Manifold Air Temperature Testing Kit



T70102

Digital Multimeter With Case and Leads - 1500 Volt DC



Voltage 200mv - 1500v DC
200mv - 1000v AC
Complete with case and leads